

INK JET RECORDING APPARATUS AND METHOD FOR
PERFORMING INK JET RECORDING

BACKGROUND OF THE INVENTION

5 Field of the Invention

Sub
B1
100221-42201

The present invention relates to an apparatus and a method for ink jet recording, which perform recording in a recording medium by discharging ink. More specifically, the invention
10 relates to an ink jet recording apparatus and a method for performing ink jet recording, which can perform recording on the full surface of the recording medium without any blank spaces.

Related Background Art

15 Conventionally, since recording operated only in a range completely coincident with the full surface of a recording sheet was not practical because of a form error of the recording sheet, a shortage of recording sheet conveying
20 accuracy in the recording apparatus side, etc., the recording operation was normally started from a place inside by a predetermined distance from the end of the recording sheet. Accordingly, the result of recording usually had spaces (margins)
25 of no recording along the end of the sheet.

However, as shown in printing services of silver salt photography, there are many who prefer

a recording result of no blank spaces (no margins) and, in the ink jet recording apparatus, some means have been put to practical use for performing recording on the full surface of the recording sheet, on which recording has already been made, without any blank spaces. Such means are largely divided into a method of processing the recording sheet after recording, and a method of compensating for the above-described error or shortage of accuracy by performing a recording operation in a range exceeding an area of the recording sheet.

As one of the former examples, a method has been available, which obtains a desired recording result by providing a region surrounded with a perforated line, and an extra portion outside this region, to be cut off along the perforated line, on the recording sheet, performing recording not only in the region surrounded with the perforated line but also even in this extra portion, and cutting off the extra portion after the end of the recording operation. An example is shown in Fig. 31. On a recording sheet 13 including a recording region 53 formed by four perforated lines 52, recording is carried out in a region exceeding the recording region 53. After the end of recording, however, extra

100221" 5522001

portions outside the recording region 53 are removed along the perforated lines 52. Thus, the result of recording on the recording sheet has no blank spaces (recording without margins) after the removal of the extra portions.

As disclosed in Japanese Patent Application Laid-Open No. 11-321016, there is a method of obtaining a desired recording result by performing recording on long roll paper, and cutting off only recorded portions after the end of the recording operation.

As one of the latter examples, regarding a recording operation performed in a range exceeding an area of the recording sheet, in order to prevent the staining of the backside of the recording sheet by ink directly discharged to a platen for holding the recording sheet, an apparatus has been put to practical use, which directly holds only the backside of the recording sheet with the platen hidden when recording is performed on a leading end or a rear end of the recording sheet.

In addition, as shown in Fig. 32, a method has been presented, which obtains a desired recording result by providing a recording sheet supporting member 50 movable in a direction similar to the scanning direction of a recording

T00221" 5E2200F

head 10, moving the recording sheet supporting member 50 while detecting a width of a recording sheet 13 by recording sheet detecting means 51, and executing recording of one line by dividing it
5 into a plurality of portions.

In the foregoing conventional examples, however, some constraints have been imposed on the execution of recording on the full surface of the recording sheet without any blank spaces.

10 Specifically, in the case of the method of processing the recording sheet after recording, it is necessary to use a recording sheet having a size larger than that of the recording sheet obtained after the recording, and the recording
15 apparatus itself must deal with such a size. Consequently, the enlargement of the recording apparatus has been inevitable. The user must process the recording sheet himself, accordingly complicating the operation. In addition, in the
20 case of the method of manually removing the extra portions of the recording sheet along the perforated line, cut surfaces are not neatly aligned, resulting in a finishing problem.

In the case of the method of cutting the
25 long roll paper after recording thereon, it is necessary to provide cutting means in the recording apparatus, resulting in increases in the

1002221"5EE22001

size and costs of the recording apparatus. In the case of the method, in which the user cuts the long roll paper after continuous image recording thereon, it is difficult to cut the paper without
5 any shifting at an image boundary, complicating the operation.

Furthermore, in the method of performing a recording operation in a range exceeding an area of the recording sheet, it is necessary to provide
10 a mechanism for moving the platen in synchronization with the conveyance of the recording sheet or a mechanism for moving the platen in synchronization with the movement of a carriage. Consequently, complication and
15 enlargement of the apparatus, and a cost increase have been inevitable.

SUMMARY OF THE INVENTION

The present invention was made to solve
20 the foregoing problems inherent in the conventional art, and it is an object of the invention to provide an ink jet recording apparatus capable of performing recording on the full surface of a recording sheet without any
25 blank spaces, and improving recording sheet finishing, and operability, without complicating or enlarging the recording apparatus, and without

200227" 3E2200F

any cost increases.

Other objects of the invention are to provide an apparatus and a method for ink jet recording, which provide a rib row including a plurality of ribs in a direction intersecting the conveying direction of a recording medium such that the ribs are disposed to be different from one another, and disposing at least two rows on a platen along the conveying direction of the recording medium when the recording medium is conveyed onto the platen disposed to face a recording head for executing recording by discharging recording liquid droplets, and ink jet recording is performed, and performing recording except for recording data corresponding to each rib position, at each of at least the two rib rows when a recording operation is performed on a leading end or a rear end of the recording medium in the conveying direction thereof, thereby completing predetermined one-line recording.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a schematic perspective view showing, in outline, an entire ink jet recording apparatus according to a first embodiment of the present invention.

Fig. 2 is a flowchart schematically

showing a recording operation of the ink jet recording apparatus of the first embodiment of the invention.

Fig. 3 is a schematic perspective view
5 showing a recording unit of the ink jet recording apparatus of the first embodiment of the invention.

Fig. 4 is a schematic side view showing the recording unit of the ink jet recording apparatus of the first embodiment of the invention.

10 Fig. 5 is a schematic side view showing the recording unit of the ink jet recording apparatus of the first embodiment of the invention.

Fig. 6 is a schematic plan view showing a recording portion of a sheet leading end of the
15 ink jet recording apparatus of the first embodiment of the invention.

Figs. 7A and 7B are schematic perspective views showing a platen portion of the ink jet recording apparatus of the first embodiment of the
20 invention.

Fig. 8 is a schematic plan view showing the recording portion of the sheet leading end of the ink jet recording apparatus of the first embodiment of the invention.

25 Fig. 9 is a schematic perspective view showing the recording unit of the ink jet recording apparatus of the first embodiment of the

FOOZET" 6E2200T

invention.

Fig. 10 is a flowchart schematically showing a recording operation of the ink jet recording apparatus of the first embodiment of the invention.

Fig. 11 is a schematic perspective view showing the recording unit of the ink jet recording apparatus of the first embodiment of the invention.

10 Fig. 12 is a schematic plan view showing
the recording portion of the sheet leading end of
the ink jet recording apparatus of the first
embodiment of the invention.

Fig. 13 is a schematic perspective view
15 showing the recording unit of the ink jet recoding
apparatus of the first embodiment of the invention.

Fig. 14 is a schematic plan view showing the recording portion of the sheet leading end of the ink jet recording apparatus of the first embodiment of the invention.

Figs. 15A, 15B and 15C are schematic plan views, each showing a discharge nozzle row of an ink jet recording apparatus according to a second embodiment of the invention.

25 Fig. 16 is a schematic perspective view
showing a platen portion of the ink jet recording
apparatus of the second embodiment of the

invention.

Fig. 17 is a view showing an ink jet recording method of the invention, seen from a conveying direction of a recording medium, when
5 the method is applied to a recording head of a full-line type.

Fig. 18 is a schematic perspective view showing a recording unit of an ink jet recording apparatus according to a third embodiment of the
10 invention.

Fig. 19 is a schematic perspective view showing the recording unit of the ink jet recording apparatus of the third embodiment of the invention.

Fig. 20 is a schematic perspective view showing the recording unit of the ink jet recording apparatus of the third embodiment of the invention.
15

Fig. 21 is a schematic perspective view showing the recording unit of the ink jet recording apparatus of the third embodiment of the invention.
20

Fig. 22 is a schematic plan view showing a recording portion of the ink jet recording apparatus of the third embodiment of the invention.
25

Fig. 23 is a schematic plan view showing the recording portion of the ink jet recording

TOP SECRET

apparatus of the third embodiment of the invention.

Fig. 24 is a flowchart schematically showing a recording operation of the ink jet recording apparatus of the third embodiment of the invention.

Fig. 25 is a flowchart schematically showing the recording operation of the ink jet recording apparatus of the third embodiment of the invention.

Fig. 26 is a schematic block diagram showing a control unit of the ink jet recording apparatus of the third embodiment of the invention.

Figs. 27A and 27B are schematic views, each showing a mask pattern of the ink jet recording apparatus of the third embodiment of the invention.

Figs. 28A, 28B, 28C, 28D, 28E, 28F and 28G are schematic plan views, each showing a recording process of an ink jet recording apparatus according to a fourth embodiment of the invention.

Fig. 29 is a schematic view showing mask patterns of the ink jet recording apparatus of the fourth embodiment of the invention.

Figs. 30A and 30B are schematic block diagrams, each showing recording data of an ink jet recording apparatus according to a fifth embodiment of the invention.

1002221-6E2200T

Fig. 31 is a schematic plan view showing a conventional example of recording with no blank spaces (recording without any margins).

Sub 33
Fig. 32 is a schematic perspective view
5 showing the conventional example of recording with no blank spaces (recoding without any margins).

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Next, description will be made of the
10 preferred embodiments of the present invention with reference to the accompanying drawings.

First Embodiment

Fig. 1 is a schematic perspective view showing an example of the entire recording unit of
15 an ink jet recording apparatus of the invention. In Fig. 1, a reference numeral 12 denotes a platen ink absorber disposed in contact with a platen; 38 a paper ejection roller gear fixed coaxially to a discharge roller 37; 39 a chassis for supporting
20 each portion of the recording apparatus; and 41 the exterior of the recording apparatus.

First, description will be made of the components and the operation of the ink jet recording apparatus by referring to Fig. 1.

25 As schematically shown, the ink jet recording apparatus of the embodiment comprises a paper feeding unit, a sheet conveying unit, a

100221" 6EE2200T

discharge unit, and a carriage unit.

The paper feeding unit includes an automatic sheet feeder (ASF) 40 for feeding recording sheets 13 as loaded recording materials
5 one by one.

Sub B4
100221-12001
~~A plurality of recording sheets 13 are stacked, and loaded on the paper feeding tray of the ASF 40. The recording sheets 13 on the paper feeding tray are separated and conveyed, starting
10 from its uppermost sheet, by the rotation a paper feed roller (not shown), and fed through a sheet conveying path (not shown) into the sheet conveying unit.~~

The sheet conveying unit includes an LF
15 roller 33 for conveying the recording sheet 13, and a pinch roller 35 disposed oppositely to the LF roller 33 to hold the recording sheet 13 with the same.

The pinch roller 35 is held by a pinch
20 roller holder 36. An LF roller 34 is fixed coaxially to the LF roller 33, and a driving force is transmitted from an LF motor (not shown) as a driving source through the LF roller gear 34 to the LF roller 33. The pinch roller 35 disposed
25 oppositely to the LF roller 33 is pressed through the pinch roller holder 36 to the LF roller 33 by an elastic member (not shown). After the

feeding-in of the recording sheet 13 by the ASF 40,
by starting the rotation of the LF roller 33, the
leading end of the recording sheet 13 is held
between the LF roller 33 and the nip portion
(contact portion) of the pinch roller 35. Since a
friction coefficient is set high between the LF
roller 33 and the recording sheet 13, the
recording sheet 13 is conveyed with almost no
slipping in correspondence with the LF roller 33.

10 The recording sheet 13 conveyed by the LF
roller 33 is guided to, and supported by a rib row
provided in the platen 11, and then guided to the
discharge unit. Each rib provided in the platen
11 to guide and support the recording sheet 13 has
15 resistance set low by reducing its contact area
with the recording sheet 13. Accordingly, the
recording sheet 13 is smoothly conveyed to the
discharge unit.

20 The discharge unit includes a discharge
roller 37 for conveying a sheet on the downstream
side of sheet conveyance, and a not-shown gear.
This gear is a driven rotor for discharging, and
provided with a number of projections in its
peripheral surface. In Fig. 12, this member is
25 disposed above the discharge roller 37.

 The discharge roller 37 is connected to
the LF roller 38 by a gear train, and adapted to

100221" 6E2200T

be rotated in synchronization. As it is similarly pressed to the discharge roller 37 by the elastic member, the gear can convey the recording sheet 13 while holding it as in the case of the LF roller.

5 Basically, the recording sheet 13 is conveyed by being held between the LF roller 33 and the pinch roller 35, and between the discharge roller 37 and the gear, and then a recording operation is performed. However, to enlarge an
10 area of a recording portion with respect to an area of the recording sheet 13, the recording operation can be performed only by holding the recording sheet between the LF roller 33 and the pinch roller 35 when recording is executed on the
15 leading end of the recording sheet 13, and between the discharge roller 37 and the gear when recording is executed on the rear end of the recording sheet 13.

The carriage unit includes a carriage 30
20 scanned by loading a recording head 10 for executing recording by discharging ink, and a guide shaft 14 and a guide rail 15 for guiding the carriage 30 to be reciprocated in a direction intersecting the conveying direction of the
25 recording sheet. The guide shaft 14 and the guide rail 15 are provided to be extended along the scanning direction of the carriage 30.

Sub
BS

100227" 6E2200T

A carriage belt 31 is attached to the carriage 30, and hung to be tense between the pulley of a carriage motor 32 as a driving source for the carriage 30 and an idler pulley attached
5 to a chassis 39. With such a constitution, the forward/backward rotation of the carriage motor 32 is converted into a reciprocating linear motion of the carriage 30.

As the recording head 10 faces the platen
10 11, recording can be executed by a line unit on the recording sheet 13 by discharging ink droplets through the ink discharge nozzle provided in the recording head 10 by a timing synchronized with the movement of the carriage 30. For the
15 recording head 10, one may be selected from a head, which includes electrothermal converting elements provided in a plurality of nozzles communicated with a common recording liquid chamber, supplies thermal energy to recording liquid in each nozzle
20 by applying an electric pulse as a recording signal to the electrothermal converting element, and uses a bubble pressure generated at the time of recording liquid bubbling caused by the state change of the recording liquid in this case for
25 discharging recording liquid droplets, a head which uses pressure energy generated by a vibrating element, e.g., a piezo element, for

100221" 6E2200T

discharging recording liquid droplets, different from the electrothermal converting element, etc.

After the end of recording on the recording sheet 13, the recording sheet 13 is
5 discharged out of the recording apparatus by the above-described discharge unit.

The components and the operation of the ink jet recording apparatus of the invention have been described.

10 Next, detailed description will be made of a recording method, especially a method of recording on the leading end and the rear end of the recording sheet 13, by referring to Figs. 2 to 12.

15 First, by using a flowchart of Fig. 2, which illustrates the recording operation on the leading end of the sheet, recording with no blank spaces (recording with no margins) on the leading end of the sheet will be described.

20 When the recording sheet 13 is conveyed, and the leading end of the recording sheet 13 is detected by a not-shown paper end (PE) sensor, a recording operation on the leading end of the sheet is started (step S1 of Fig. 2).

25 Then, to cue the leading end of the recording sheet 13 to a predetermined position, the LF motor is driven to rotate the LF roller

1002233 12001

SECRET

SECRET

SECRET

of the discharge nozzle row 16b, and located before the most downstream side of the discharge nozzle row 16b by a distance L_b . A reason for setting such a distance L_b is as follows. That is, if the conveying of the recording sheet is in an ideal state, and the relative positions of the leading end of the recording sheet 13 and the discharge nozzle of the recording head 10 can be established, then by starting the recording operation from the head portion of the recording sheet 13 with $L_b=0$, it is possible to perform recording with no blank spaces in the leading end. In actuality, however, there may be a shortage of accuracy of the PE sensor for detecting the position of the recording sheet, or there may be a loss of parallelism between the leading end part of the recording sheet and the scanning direction of the carriage 30 caused by the slightly oblique conveying of the recording sheet. Thus, with $L_b=0$, small blank spaces may be generated in the leading end, or unexpected discharging of ink droplets to the outside of the recording sheet may occur. It is not impossible to devise means for completely preventing such a problem, but it is not advisable to adopt such means because of cost consideration.

As described above, by setting a proper distance L_b , even if certain variance occurs in

various accuracies, it is possible to assure that the leading end of the recording sheet 13 is always in the region of the discharge nozzle row 16b. No blank spaces are generated in the leading
5 end.

In the described case, data necessary for recording must be foreseen, including one regarding the distance Lb. In actual practice, therefore, it is necessary to prepare data of a
10 region slightly larger than that to be recorded on the recording sheet.

After the end of the cuing of the recording sheet carried out in the foregoing manner, a recording operation is started in next
15 step.

Subsequently, processing for masking the second region (region indicated by a reference numeral 15 in Fig. 8) of the leading end recording data is carried out (step S3 in Fig. 2). This
20 processing is for executing recording on the leading end by dividing it into a plurality of paths. Fig. 6 is a schematic plan view showing the method of masking the leading end recording data. In the drawing, a reference numeral 17
25 denotes the entire range of the leading end recording data; and 18 the first region of the leading end recording data.

Sub B7
SECRET

In the masking of step S3, since only the first region 18 of the leading end recording data is recorded with respect to the leading end recording data 17 of one line, a remaining portion
5 must be masked so as not to be recorded. That is, for example, AND is obtained from the leading end recording data fed in from the host computer, and the mask of the first region 18 of the leading end recording data, and only the recording data of a
10 portion indicated by a hatched line in Fig. 6 is set as valid recording data.

Here, the first region 18 of the leading end recording data is set in correlation with the arrangement of the rib row provided in the platen
15 11. To explain this correlation with the arrangement of the rib row, a platen form will now be described.

Figs. 7A and 7B are schematic perspective views, each showing a relation between the platen
20 11 and the platen ink absorber 12. For the foregoing reason, the ribs are provided in the platen and, according to the invention, a plurality of rib rows are provided. As shown in Figs. 3 to 7A, the platen 11 includes a platen rib
25 row B11b composed of ribs, which are arrayed roughly at equal intervals up to about half of the upstream side of the recording sheet conveying

100221" 6E2200T

Sub
B3

Sub B8 (C mid)
FOUO 221 5522001

direction X, and a platen rib row Alla composed of ribs, which are arrayed up to about half of the downstream side of the recording sheet conveying direction X such that each rib is disposed roughly in the center between the ribs of the platen rib row B11b. In addition, when seen from the recording sheet conveying direction X, as shown in Fig. 4, the platen rib row B11b is disposed up to about half of the upstream side of the discharge nozzle row 16, and the platen rib row Alla is disposed up to about half of the downstream side of the discharge nozzle row 16.

In the platen 11 having such rib arrays, the platen ink absorber 12 is disposed in such a way as to fill portions other than the ribs. The platen ink absorber 12 is made of a material such as pipe or high polymer, having good ink absorbing efficiency, and has hole bored in portions corresponding to the ribs of the platen 11.

By combining the platen 11 with the platen ink absorber 12, a unit shown in Fig. 7A is formed, which is disposed in the recording apparatus.

On the platen 11 having the ribs disposed roughly in a staggered form as described above, the first region 18 of the leading end recording data is set in correspondence with the pitch of the platen rib row B11b of the upstream side.

Sub B8 (concl.)
More specifically, the first region 18 of the leading end recording data is set in such a way as to be disposed roughly in the center between the ribs of the platen rib row B11b (Fig. 6).

5 Accordingly, the pitch of the first region 18 of the leading end recording data substantially coincides with that of the platen rib row B11b, and its width is about half of the pitch of the platen rib row B11b.

10 The relation between the rib row of the platen 11 and the first region 18 of the leading end recording data has been described.

Sub B8
Subsequently, the first region 18 is scanned by the first scanning of the carriage 30 (step S4 of Fig. 2). Specifically, as described above, the carriage 30 is driven, and scanned, and the recording operation is performed based on the masked recording data. Ink droplets discharged from the discharge nozzle of the recording head 10

20 land on the recording sheet 13 to be fixed. However, as shown in Fig. 4, since the discharge nozzle row 16b includes the discharge nozzle not facing the recording sheet 13 by the distance Lb, ink droplets discharged therefrom directly reach the platen ink absorber 12 to be absorbed and recovered. In addition, as shown in Fig. 16, for the recording of the first region 18, ink droplets

are discharged from a portion having no platen rib
row B11b. Accordingly, no ink droplets are
discharged onto the platen rib B11b. Moreover,
since the region that corresponds to the first
5 region 18 of the leading end recording data is
only that of the discharge nozzle row 16b, no ink
droplets are discharged onto the platen rib row
A11a, and ink droplets discharged outside the
recording sheet 13 are all absorbed and recovered
10 by the platen ink absorber 12.

A reason for the discharging of no ink
droplets on the ribs of the platen 11 by the
foregoing method is as follows. That is, since
the recording sheet 13 is conveyed while being
15 guided by the ribs, the opposite recording surface
side of the backside of the recording sheet 13,
and the ribs of the platen 11 are slid and, if
there are ink droplets stuck on the ribs of the
platen 11, the opposite recording surface side of
20 the recording sheet 13 may be stained by ink.

Fig. 3 shows a state after the end of the
one-line recording operation. A first recording
region 13a is formed on the recording sheet 13 by
first scanning.

25 Subsequently, the recording sheet 13 is
conveyed by a predetermined amount (step S5 of Fig.
2). By referring to Fig. 5, which shows a state

Sub
B9
(Circ.)

100221"5E22007

Sub
B10

Sub
B10
(Coul.)

after the conveyance of the recording sheet 13, it
can be understood that the leading end portion of
the recording sheet 13 after step S5 is located
within the range of the discharge nozzle row 16a,
5 and conveyed from the most downstream side of the
discharge nozzle row 16a to the leading end of the
recording sheet 13, away by a distance La. A
reason for such a distance La is completely
similar to that for the distance Lb described
10 above with reference to Fig. 4. In addition, a
conveying amount is preferably be set equal to
half or lower of a length of the discharge nozzle
row 16 in the recording sheet conveying direction
X. Thus, the length of the discharge nozzle
15 length can be used highly efficiently.

Then, the first region 18 of the leading
end recording data is masked (step S6 of Fig. 2).
This masking is carried out for recording portions
left unrecorded in the recording in steps S3 and
20 S4.

Fig. 8 is a schematic plan view showing a
second masking method of the leading end recording
data. In the drawing, a reference numeral 19
denotes a second region of the leading end
25 recording data. In the masking of step S6, since
a portion left unrecorded in the masking of step
S3 is recorded, the second region 19 of the

100221" 6E2200F

leading end recording data is a region obtained by reversing (removing) the first region 18 of the leading end recording data with respect to the leading end recording data 17. As in the case of
5 step S4, AND is obtained from the leading end recording data 17 and the mask of the second region 19 of the leading end recording data, and only recording data of a portion indicated by a hatched line in Fig. 8 is set as valid recording
10 data.

Subsequently, the second region 19 is scanned by the second scanning of the carriage 30 (step S7 of Fig. 2). This scanning may be carried out by the first scanning during returning in step
15 S4, or by returning to the start of the first scanning, and then scanning in the same direction as that for the first scanning. In this case, a portion of the valid recording data where ink droplets are discharged to the outside of the
20 recording sheet 13 is between the ribs of the platen rib row Alla because of a relation between the setting of the first region 18 of the leading end recording data and the platen rib rows Alla and B11b. Accordingly, no ink droplets are
25 discharged onto the platen rib row Alla. As a result, ink droplets discharged outside the recording sheet 13 are all absorbed and recovered

Sub
B11b
100221-12001

Sub
B11
(cont.)

~~by the platen ink absorber 12.~~

Fig. 9 shows a state after the end of the second scanning in the one-line recording operation. By forming a second recording region 13b on the recording sheet 13 by the second scanning, coupled with the first recording region 13a, one-line recording of the leading end recording data 17 is completed.

The method of recording with no blank spaces in the leading end of the sheet has been described.

In the foregoing, the description was made particularly of the recording with no blank spaces (recording with no margins) in the leading end portion of the recording sheet 13. In Figs. 3, 6, 8 and 9 referenced above, recording is also made simultaneously with no blank spaces in the left and right ends, and thus this recording will be described.

Regarding recording with no blank spaces (recording with no margins) in the left and right ends of the recording sheet 13, if the carriage scanning direction positions of the recording sheet 13 and the carriage 30 are in ideal states, it is possible to perform recording with no blank spaces by executing recording to the limit of the sheet end.

100221" 6E2200T

In an actual case, however, because of dependence on the sheet setting accuracy or the like in the left and right directions by the user, ideal states are frequently far from being realized. To avoid such a problem, means can be taken to perform recording by using a sensor or the like to detect the left/right end position of the recording sheet 13. However, such means is not advisable if consideration is given to costs.

10 Thus, by setting a real recording region width equal to/higher than the width of the recording sheet 13, it is realistic to perform recording with no blank spaces (recording with no margins) by discharging some ink droplets to the outside of

15 the recording sheet 13. This system is also employed in the described embodiment.

Specifically, recording data is set to be wider than the set size of the recording sheet 13 by amounts LL and LR shown in Fig. 8. In the

20 regions of LL and LR, the arrangements of the rib rows are predetermined so as to prevent the presence of ribs on the platen 11. This constitution prevents the sticking of ink droplets on the ribs of the platen 11 even if ink droplets

25 are discharged outside the left or right end of the recording sheet, thereby enabling recording with no blank spaces (recording with no margins)

1002221-6E22001

to be performed. In addition, as recording data,
it is necessary to prepare data having a length,
which is obtained by adding LL and LR to the width
of the recording sheet 13. In the case of this
5 constitution, when a recording sheet having an
unknown sheet width is inserted, although ink
droplets may be stuck to the ribs of the platen 11,
the sheets of standardized sizes are used in most
cases, and thus there are no problems for
10 practical purposes.

Next, description will be made of
recording with no blank spaces (recording with no
margins) in the rear end portion of the sheet by
referring to the flowchart of Fig. 10 illustrating
15 the recording operation of the rear end portion of
the sheet.

When the rear end of the recording sheet
13 being conveyed is detected by a not-shown paper
end (PE) sensor, a recording operation is started
20 on the rear end portion of the sheet (step S11 of
Fig. 10). During the recording operation on the
full surface of the sheet, the rear end portion of
the recording sheet 13 is detected during the
recording sheet conveyance in the middle of the
25 recording operation, and thus the position of
detecting the sheet rear end is stored in the
memory of the control circuit for the recording

1002221 5522001

apparatus.

Sub
B12

Then, determination is made as to the conveyance of the recording sheet 13 by a predetermined amount from the recording sheet rear end position previously detected and stored in the memory (step S12 of Fig. 10). Specifically, determination is made as to whether the rear end portion of the recording sheet 13 is in the range of the discharge nozzle row 16b or not. If the sheet rear end is determined to be in this range, then the process proceeds to next step.

10022" 6E2200F

Subsequently, the second region of the rear end recording data (region indicated by a reference numeral 29 in Fig. 14) is masked (step S13 of Fig. 10). Specific means is almost similar to that of the recording with no blank spaces in the sheet leading end, and thus only brief description will be made. That is, the recording data to be masked in this step is one located in the place of the same phase as that for the platen rib row B11b (Fig. 12).

Also for the recording end portion, it is necessary to prepare recording data having a length longer than that of the recording sheet 13 by foreseeing ink droplets to be discharged to the outside of the recording sheet 13.

Sub
B13

~~Then, a first region 28 is recorded by the~~

Sub
B13
(cnc)

first scanning of the carriage 30 (step S14 of Fig. 10). The recording operation is similar to that for the recording with no blank spaces in the sheet leading end (see Fig. 12). Thus, the sticking of ink droplets onto the platen rib row B11b is prevented, and ink droplets discharged to the outside of the recording sheet 13 are directly absorbed and recovered by the platen ink absorber 12. Fig. 11 shows a state after the end of this recording operation of one line. As indicated by a hatched line, an integrated recording region 13c is formed by integrating the region recorded before the sheet rear end recording with the first recording region by the first scanning on the recording sheet 13.

Subsequently, the recording sheet 13 is conveyed by a predetermined amount (step S15 of Fig. 10). The rear end of the recording sheet 13 after the conveyance by the predetermined amount is within the range of the discharge nozzle row 16a as shown in Fig. 14, and the amount of conveyance in this case should preferably be set equal to/lower than half of the length of the discharge nozzle row 16 in the recording sheet conveying direction X.

Then, the first region 28 of the rear end recording data is masked (step S16 of Fig. 10).

This masking is carried out for recording a portion unrecorded in steps S13 and S14. In other words, the recording data to be masked in this step is data located in the place of the same
5 phase as that for the platen rib row Alla (Fig. 14).

Sub
24
FOOT "SEE 2001"

Then, a second region 29 is recorded by the second scanning of the carriage 30 (step S17 of Fig. 10). The recording operation is similar
10 to that for recording with no blank spaces (recording with no margins) in the sheet leading end (see Fig. 14). Thus, the sticking of ink droplets onto the platen rib row Alla is prevented, and ink droplets discharged to the outside of the
15 recording sheet 13 are directly absorbed and recovered by the platen ink absorber 12. Fig. 13 shows a state after the end of the recording operation of one line, where the integrated recording region 13c already recorded by step S14
20 is integrated with a last recording region 13d recorded in step S17, thereby completing the recording on the full surface of the recording sheet 13.

Then, the recording sheet 13 is expelled
25 out of the recording apparatus (step S18 of Fig. 10). The expelling operation is carried out cooperatively by the discharge roller 37 and the

not-shown gear as described above.

The method of recording with no blank spaces in the sheet rear end portion has been described.

5 Therefore, since recording with no blank spaces in the leading end, in the left and right ends, and in the rear end can be performed, it is possible to carry out recording with no blank spaces on the full surface of a predetermined
10 recording sheet.

 In the embodiment, the ribs of the platen rib row are arrayed at equal intervals. However, the invention is not limited to such an arrangement, and the ribs may be arranged at
15 ununiform intervals.

5300221" SEE 2200T
3/5
~~In such a case, each rib of the platen rib row A11a may be disposed between the adjacent ribs of the platen rib row B11b or roughly in the center, the first and second regions 18 and 19 of
20 the leading end recording data may respectively be set between the ribs of the platen rib rows B11b and A11a or roughly in the centers, and a width of each in this case may be set about half of the rib interval.~~

25 In the embodiment, the one-line recording/feeding was carried out by a width equivalent to nearly 1/2 of the length of the

discharge nozzle row 16 during the recording of
the sheet leading end portion or the sheet rear
end portion. However, the invention is not
limited to such, and one-line recording/feeding
5 may be carried out by a length equal to/lower than
1/2 of the length of the discharge nozzle row 16.
This is very effective in that especially when
wishing to obtain recording resolution equal
to/higher than the real resolution of the
10 discharge nozzle row or the like, it can be
realized by recording the same region in an
interlacing manner by a plurality of line-feeding
operations.

In addition, in the embodiment, the width
15 of the discharge nozzle row 16 was divided into
the two portions, i.e., the place indicated by the
reference numeral 16a:the place indicated by the
reference numeral 16b \approx 1:1. However, the
invention is not limited to such, and the width
20 may be divided into three or more portions, or an
ununiform division ratio may be set.

As apparent from the foregoing, by
constructing the ink jet recording apparatus
according to the embodiment, it is possible to
25 perform recording on the full surface of the
recording sheet with no blank spaces without any
complication or enlargement of the recording

1002221"5E2200T

apparatus, and without any cost increases. To obtain a recording result with no blank spaces, it is not necessary for the user himself to perform secondary processing after the recording operation, thus improving operability. Moreover, since no secondary processing is necessary for the recording sheet after the recording operation to obtain a recording result with no blank spaces, it is possible to obtain a very beautiful recording result without any degradation of recording sheet finishing.

Second Embodiment

In the foregoing first embodiment, the case of only one discharge nozzle row of the recording head was shown. However, the invention is not limited to such a case, and it can be applied to a case where the recording head includes a plurality of discharge nozzle rows.

In the section, the second embodiment will be described with reference to the accompanying drawings. Here, the description will focus on points different from the first embodiment.

Figs. 15A to 15C are schematic plan views, each showing the discharge nozzle face of a recording head including a plurality of discharge nozzle rows. In the drawings, a reference numeral 42 denotes the discharge nozzle face of the

recording head when seen from the recording sheet side; 43 the discharge nozzle row B of black ink; 44 the discharge nozzle row Y of yellow ink; 45 the discharge nozzle row M of magenta ink; and 46 the discharge nozzle row C of cyan ink. The upper and lower direction of Fig. 13 is a recording sheet conveying direction X, and a left and right direction with respect to the sheet surface is a carriage scanning direction Y.

10 First, description will be made of a case where a plurality of discharge nozzle rows are arrayed in a horizontal direction (roughly parallel to the carriage scanning direction).

Fig. 15A shows an example of the case
15 where the plurality of discharge nozzle rows are arrayed in the horizontal direction. In this case, a recording process regarding recording with no blank spaces (recording with no margins) in the leading end and the rear end is substantially
20 similar to that of the first embodiment. However, when recording from all the discharge nozzles is carried out by one scanning of the carriage, it is advisable to perform sheet conveyance control in such a way as to position the leading end or the
25 rear end of the recording sheet in a region described below. That is, a region where the plurality of discharge nozzle rows B, Y and C are

1002221 6E2200T

present in common in the recording sheet conveying direction is treated equally to the discharge nozzle row 16 region (see Figs. 5, 8, etc.) of the first embodiment. This common region is divided into two portions roughly at the center thereof, and these portions are set as nozzle rows A and B. In addition, a rib row disposed on the platen is also divided into two rows roughly at the center of the common region.

10 With the foregoing constitution, when the leading end or the rear end portion of the recording sheet is recorded, sheet conveyance control is performed such that the end portions stops at least once each in the regions LA and LB. 15 Thus, it is possible to perform recording with no blank spaces on the full surfaces of the recording sheet.

Next, description will be made of a case where a plurality of nozzle rows are arrayed in a longitudinal direction (straight line along the sheet conveying direction). 20

Fig. 15B shows an example where the plurality of nozzle rows are arrayed in the longitudinal direction. In this case, sheet conveyance control and the rib row arrangement of the platen become a little complex. That is, in 25 the case of the sheet conveyance control, the

FIG. 15B

control described above with reference to the first embodiment is carried out for each discharge nozzle row, and the control is repeated according to the number of discharge nozzle rows.

- 5 Specifically, a discharge nozzle row B43 is divided into regions LBA and LBB; a discharge nozzle row C46 into regions LCA and LCB; a discharge nozzle row M45 into regions LMA and LMB; and a discharge nozzle row Y44 into regions LYA
10 and LYB.

The rib row disposed on the platen may also be divided roughly at the center of each discharge nozzle row. According to the embodiment, the rib row of the platen can be divided into five
15 by setting common the divided regions of the adjacent discharge nozzle rows.

Fig. 16 shows an example of the rib row of the platen, which is divided into five. In the drawing, reference numerals 11c, 11d, 11e, 11f,
20 and 11g respectively denote platen rib rows C, D, E, F and G.

In the embodiment, the region of the discharge nozzle row B43 is not divided at the center. The region division can be made somewhere
25 in the discharge nozzle row, and it is not always divided at the center. The same can be said of the division of the rib row of the platen. With

the foregoing constitution, when the leading end
of the rear end portion of the recording sheet is
recorded, it is advisable to perform sheet
conveyance control such that the end portion stops
5 at least once each in the divided regions LBB, LBA,
LCB, LCA, LMB, LMA, LYB and LYA of the discharge
nozzle row. Accordingly, it is possible to
perform recording with no blank spaces on the full
surface of the recording sheet.

10 Next, description will be made of a case
where a plurality of nozzle rows are partially
arrayed in longitudinal and horizontal directions.
Fig. 15C shows an example where the plurality of
discharge nozzle rows are arrayed in the
15 longitudinal and horizontal directions. In this
case, the arrangement is basically similar to the
longitudinal array of Fig. 15B. Specifically, the
discharge nozzle row C46 is divided into regions
LAC and LCB; the discharge nozzle row 45 into
20 regions LMA and LMB; and the discharge nozzle row
Y44 into regions LYA and LYB. The discharge
nozzle row B43 should preferably be divided at the
same phase as that for the dividing position of
any one of the discharge nozzle rows arrayed in
25 the horizontal direction.

In addition, regarding the rib rows of the
paten, division may be made roughly at the center

Sub
B18
(Contd)

of each of the discharge nozzle rows Y44, M45, and C46. According to the embodiment, the number of ribs of the platen can be set to four by making common the divided regions of the adjacent
5 discharge nozzle rows.

With the foregoing constitution, when the leading end or the rear end portion of the recording sheet is recorded, it is advisable to perform sheet conveyance control such that the
10 sheet end portions at least one each in the regions LCB, LCA, LMB, LMA, LYB and LYA. Accordingly, it is possible to perform recording with no blank spaces on the full surface of the recording sheet.

15 As apparent from the foregoing, with the ink jet recording apparatus constructed according to the embodiment, even in the case of the recording head including the plurality of discharge nozzle rows, it is possible to perform
20 recording with no blank spaces on the full surface of the recording sheet without any complication or enlargement of the recording apparatus, and without any cost increases.

Sub
B19

25 In the foregoing first and second embodiments, reference was made to the example of the so-called serial type recording apparatus, which performs recording by conveying the

Sub
B3
(Cont'd)

100221" 5E22001

5 recording medium, and scanning the recording head
in the direction intersecting the recording medium
conveying direction. However, the invention is
not limited to such, and it can be applied to a
so-called full line type recording apparatus, in
10 which the recording head includes a discharge port
row corresponding to the full width of the
recording medium. For example, as shown in Figs.
7A and 7B of the recording apparatus of the
invention seen from the recording medium conveying
15 direction, even if the recording head 10 of the
serial type shown in Figs. 3, 9, 11, 13, etc., is
changed to the recording head of the full line
type, it is possible to execute a recording method
similar to that described above with reference to
each of the embodiments.

Further, the invention can also be applied
to a recording apparatus, in which instead of the
recording head of the full line type limited to
20 single color, a plurality of full line type
recording heads independent for individual colors
are provided in the recording medium conveying
direction, and image recording of a plurality of
colors, e.g., magenta, cyan, yellow, black, etc.,
25 can be performed.

As apparent from the foregoing, according
to each of the embodiments, it is possible to

5 In addition, since it is not necessary for the user himself to perform any secondary processing after the recording operation to obtain a recording result with no blank spaces, operability can be improved.

Third Embodiment

First, description will be made of recording with no blank spaces in the leading end portion of the sheet by referring to the flowchart of Fig. 24 illustrating the recording operation on the leading end portion of the sheet.

In step S21, when the leading end of the recording sheet is detected by a not-shown paper end (PE) sensor, a recording operation on the leading end of the sheet is started.

5 Then, in next step S22, to cue the leading
end of the recording sheet 13 to a predetermined
position, the LF motor is driven to rotate the LF
roller forward. The predetermined position means
a position satisfying a relation between the
10 recording head 10 and the recording sheet 13 shown
in Fig. 18. Here, to clarify a positional
relation, Fig. 4 shows a schematic side view of
the recording apparatus when seen from the arrow
direction A of Fig. 1. In the drawing, a
15 reference numeral 16 denotes an ink discharge
nozzle row provided in the recording head 10. The
discharge nozzle row 16 includes a plurality of
nozzles arrayed roughly linearly, and a roughly
half of the upstream side thereof in a sheet
20 conveying direction is called a discharge nozzle
row 16b. Similarly, as shown in Fig. 5, roughly a
half of the downstream side thereof in the sheet
conveying direction is called a discharge nozzle
row 16a.

25 The predetermined position for cuing
during the recording operation on the leading end
of the sheet indicates a state, where the leading

Sub
B20

FIG. 4

end of the recording sheet 13 is within the range of the discharge nozzle row 16b, and located before the most downstream side of the discharge nozzle row 16b by a distance L_b . A reason for setting such a distance L_b is as follows. That is, if the conveying of the recording sheet is in an ideal state, and the relative positions of the leading end of the recording sheet 13 and the discharge nozzle of the recording head 10 can be established, then by starting the recording operation from the head portion of the recording sheet 13 with $L_b=0$, it is possible to perform recording with no blank spaces in the leading end. In actuality, however, there may be a shortage of accuracy of the PE sensor for detecting the position of the recording sheet, or there may be a loss of parallelism between the leading end part of the recording sheet and the scanning direction of the carriage 30 caused by the slightly oblique conveying of the recording sheet 13. Thus, with $L_b=0$, small blank spaces may be generated in the leading end, or unexpected discharging of ink droplets to the outside of the recording sheet may occur. It is not impossible to devise means for completely preventing such a problem, but it is not advisable to adopt such means because of cost consideration. As described above, by setting a

proper distance Lb, even if certain variance occurs in various accuracies, it is possible to assure that the leading end of the recording sheet 13 is always in the region of the discharge nozzle row 16b. Thus, no blank spaces are generated in the leading end.

Sub B22
100221-622201

In the described case, data necessary for recording must be foreseen, including one regarding the distance Lb. In actual practice, therefore, it is necessary to prepare data of a region slightly larger than that to be recorded on the recording sheet. After the end of the cuing of the recording sheet carried out in the foregoing manner, a recording operation is started in next step.

Sub B22
100221-622201

Subsequently, in step S23, processing for masking the second region of the leading end recording data is carried out. This processing is for executing recording on the leading end by dividing it into a plurality of paths.

Sub B22

Fig. 22 is a schematic plan view showing the method of masking the leading end recording data. In the drawing, a reference numeral 117 denotes the entire range of the leading end recording data; and 118 the first region of the leading end recording data. The data first region 118 is composed of a first region signal portion

Sub
B22
(Cont.)

~~118a not superposed by a later-described second region of the reading end recording data, and a first region superposed portion 118b superposed by the second region of the leading end recording~~
5 data.

10 In the masking of step S23, since only the first region 118 of the leading end recording data is recorded with respect to the leading end recording data 117 of one line, a remaining portion must be masked so as not to be recorded. That is, AND is taken from the leading end recording data fed in from the host computer or the like, and the mask of the first region 18 of the leading end recording data, and only the
15 recording data of a portion indicated by a hatched line in Fig. 22 is set as valid recording data.

Here, original 100% of the recording data of the first region single portion 118a is recorded, while the first region superposed
20 portion 118b is processed by using a random mask pattern. This is attributed to the fact that as described later, since the first and second regions 118 and 119 of the leading end recording data are recorded during the scanning of different
25 recording heads 10, in the boundary thereof, a small gap may occur because dots formed by ink droplets are not filled, i.e., so-called white

1002221" 5EE2200T

line, or conversely the landing of ink droplets on the same plate may occur, i.e., black line. The occurrence of such a white or black line depends on the conveying accuracy of the carriage 30, the conveying accuracy of the recording sheet 13, the form of the recording sheet, etc., it is very difficult to reduce the occurrence to zero. As a technology for reducing visual influence on the recording result by such an error, random masking is carried out. This technology makes use of a visual characteristic that gaps or superposing occurring in a random position are difficult to be seen by human eyes, while dot gaps or superposing arrayed on a straight line are easily seen by human eyes.

Next, description will be made of specific means of random masking. Fig. 26 is a block diagram showing the electric circuit rigidity of the ink jet recording apparatus of the invention; and Figs 27A and 27B examples of 4×4 dot random access patterns. In the embodiment, a pattern of 50% duty is first used, and then a complementary pattern of 50% is used, thus obtaining a 100% recording duty at the end. This duty distribution may be optionally set as long as a total result is 100% at the end. For pattern generation, a method of generation by using random numbers may be used

as occasion demands. Alternatively, patterns may be stored beforehand in a ROM 63 or a RAM 64, and one may be selected to be used.

When the first region superposed portion
5 118b is recorded, one shown in Fig. 27A is used as a random mask pattern. AND is taken between a place indicated by a black circle in the drawing and the recording data to be set as discharge data, and this data is transferred through a data
10 transfer circuit 66 to a recording head driver 67.

Here, the first region 118 of the leading end recording data 118 is set as data having a block form synchronized with the arrangement of the rib rows provided in the platen 11. To
15 explain how a data block is formed in synchronization with the arrangement of the rib rows, the platen form will be described next.

Figs. 7A and 7B are schematic perspective views, each showing a relation between the platen
20 11 and the platen ink absorber 12. For the foregoing reason, the ribs are provided in the platen and, according to the invention, a plurality of rib rows are provided. As shown in Fig. 7A, the platen 11 includes a platen rib row
25 11b composed of ribs, which are arrayed roughly at equal intervals up to about half of the upstream side of the recording sheet conveying direction,

Sub 1323
FOOT

Sub
B23
(Cont'd)

and a platen rib row 11a composed of ribs, which
are arrayed up to about half of the downstream
side of the recording sheet conveying direction
such that each rib is disposed roughly in the
5 center between the ribs of the platen rib row 11b.
In addition, when seen from the recording sheet
conveying direction, as shown in Fig. 5, the
platen rib row 11b is disposed up to about half of
the upstream side of the discharge nozzle row 16,
10 and the platen rib row 11a is disposed up to about
half of the downstream side of the discharge
nozzle row 16. In the platen 11 having such rib
arrays, the platen ink absorber 12 is disposed in
such a way as to fill portions other than the ribs.

Sub
C2

15 The platen ink absorber 12 is made of a
material such as pipe or high polymer, having good
ink absorbing efficiency, and has hole bored in
portions corresponding to the ribs of the platen
11. By combining the platen 11 with the platen
20 ink absorber 12, a unit shown in Fig. 7B is formed,
which is disposed in the recording apparatus.

On the platen 11 having the ribs disposed
roughly in a staggered form as described above,
the first region 118 of the leading end recording
25 data is set in correspondence with the pitch of
the platen rib row 11b of the upstream side. More
specifically, the first region 118 of the leading

end recording data is set in such a way as to be disposed roughly in the center between the ribs of the platen rib row 11b. Accordingly, the pitch of the first region 118 of the leading end recording data substantially coincides with that of the
5 platen rib row 11b, and its width is about half of the pitch of the platen rib row 11b.

The relation between the rib row of the platen 11 and the first region 118 of the leading
10 end recording data has been described.

Subsequently, in step S24, the first region is scanned by the first scanning of the carriage 30. Specifically, as described above, the carriage 30 is driven, and scanned, and the
15 recording operation is performed based on the masked recording data. Ink droplets discharged from the discharge nozzle of the recording head 10 land on the recording sheet 13 to be fixed. However, as shown in Fig. 4, since the discharge
20 nozzle row 16b includes the discharge nozzle not facing the recording sheet 13 by the distance Lb, ink droplets discharged therefrom directly reach the platen ink absorber 12 to be absorbed and recovered. In addition, for the recording of the
25 first region, ink droplets are discharged only from a portion having no platen rib row 11b. Accordingly, no ink droplets are discharged onto

100-22-200T

S24
24

Sub
B24
(Cont'd)

the platen rib 11b. Moreover, as shown in Fig. 22, since the region that corresponds to the first region of the leading end recording data is only that of the discharge nozzle row 16b, no ink droplets are discharged onto the platen rib row 11a, and ink droplets discharged outside the recording sheet 13 are all absorbed and recovered by the platen ink absorber 12.

10 A reason for the discharging of no ink droplets on the ribs of the platen 11 by the foregoing method is as follows.

Sub
B25

That is, since the recording sheet 13 is conveyed while being guided by the ribs, the opposite recording surface side of the backside of the recording sheet 13, and the ribs of the platen 11 are slid and, if there are ink droplets stuck on the ribs of the platen 11, the opposite recording surface side of the recording sheet 13 may be stained by ink.

20 Fig. 18 shows a state after the end of the one-line recording operation. A first recording region 13a is formed on the recording sheet 13 by first scanning.

Sub
B26

25 Subsequently, in step S25, the recording sheet 13 is conveyed by a predetermined amount. Fig. 5 shows a state after the conveyance of the recording sheet 13. In this case, the leading end

Sub
B26
(Contd)

100222T 6E2200T

portion of the recording sheet 13 is located within the range of the discharge nozzle row 16a, and conveyed from the most downstream side of the discharge nozzle row 16a to the leading end of the recording sheet 13, away by a distance La. A reason for such a distance La is completely similar to that for the distance Lb described above with reference to Fig. 4. In addition, a conveying amount is preferably be set equal to half or lower of a length of the discharge nozzle row 16 in the recording sheet conveying direction. Thus, the length of the discharge nozzle length can be used highly efficiently.

Then, in step S26, the first region of the leading end recording data is masked. This masking is carried out for recording portions left unrecorded in the recording in steps S23 and S24. Fig. 23 is a schematic plan view showing a second masking method of the leading end recording data. In the drawing, a reference numeral 119 denotes a second region of the leading end recording data. The data second region 119 is composed of a second region single portion 119a not superposed by the above-described data first region 118, and a second region superposed portion 119b superposed by the first region superposed portion 118b.

In the masking of step S26, since a

portion left unrecorded in the masking of step S23 is recorded, the second region 119 of the leading end recording data is a region obtained by reversing the first region 118 of the leading end recording data with respect to the leading end recording data 117. As in the case of step S24, AND is taken from the leading end recording data 117 and the mask of the second region of the leading end recording data, and only recording data of a portion indicated by a hatched line in Fig. 23 is set as valid recording data.

That is, for the second region superposed portion 119b, a random mask pattern shown in Fig. 27B is used. AND is taken between a place indicated by a black circle in the drawing and the recording data to be set as discharge data, and this data is transferred through the data transfer circuit 66 to the recording head driver 67. By performing such a recording operation, a dot unrecorded during the recording head scanning in step S24 is recorded in a complementary manner, assuring recording of original 100% data.

Here, as can be understood from Figs. 22 and 23, because of the presence of the first and second region superposed portions 118 and 119b, the total length of the recording data block in the main scanning direction

FIG. 23

$L_{total} = (L1 + L2 + L3 + L4 + L5 + L6 + L7 + L8 + L9 + L10) + (L11 + L12 + L13 + L14 + L15 + L16 + L17 + L18 + L19 + L20)$ satisfies $L_{total} > L$ in a relation with the valid recording length L of the main scanning direction.

5 Subsequently, in step S27, the second region is scanned by the second scanning of the carriage 30. This scanning may be carried out by the first scanning during returning in step S4, or by returning to the start of the first scanning,
10 and then scanning in the same direction as that for the first scanning. In this case, a portion of the valid recording data where ink droplets are discharged to the outside of the recording sheet 13 is between the ribs of the platen rib row 11a because of a relation between the setting of the
15 first region 118 of the leading end recording data and the platen rib rows 11a and 11b. Accordingly, no ink droplets are discharged onto the platen rib row 11a. As a result, ink droplets discharged
20 outside the recording sheet 13 are all absorbed and recovered by the platen ink absorber 12.

Sub B27

Fig. 19 shows a state after the end of the second scanning in the one-line recording operation. By forming a second recording region
25 113b on the recording sheet 13 by the second scanning, coupled with the first recording region 113a, one-line recording of the leading end

10
 11
 12
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100
 101
 102
 103
 104
 105
 106
 107
 108
 109
 110
 111
 112
 113
 114
 115
 116
 117
 118
 119
 120
 121
 122
 123
 124
 125
 126
 127
 128
 129
 130
 131
 132
 133
 134
 135
 136
 137
 138
 139
 140
 141
 142
 143
 144
 145
 146
 147
 148
 149
 150
 151
 152
 153
 154
 155
 156
 157
 158
 159
 160
 161
 162
 163
 164
 165
 166
 167
 168
 169
 170
 171
 172
 173
 174
 175
 176
 177
 178
 179
 180
 181
 182
 183
 184
 185
 186
 187
 188
 189
 190
 191
 192
 193
 194
 195
 196
 197
 198
 199
 200
 201
 202
 203
 204
 205
 206
 207
 208
 209
 210
 211
 212
 213
 214
 215
 216
 217
 218
 219
 220
 221
 222
 223
 224
 225
 226
 227
 228
 229
 230
 231
 232
 233
 234
 235
 236
 237
 238
 239
 240
 241
 242
 243
 244
 245
 246
 247
 248
 249
 250
 251
 252
 253
 254
 255
 256
 257
 258
 259
 260
 261
 262
 263
 264
 265
 266
 267
 268
 269
 270
 271
 272
 273
 274
 275
 276
 277
 278
 279
 280
 281
 282
 283
 284
 285
 286
 287
 288
 289
 290
 291
 292
 293
 294
 295
 296
 297
 298
 299
 300
 301
 302
 303
 304
 305
 306
 307
 308
 309
 310
 311
 312
 313
 314
 315
 316
 317
 318
 319
 320
 321
 322
 323
 324
 325
 326
 327
 328
 329
 330
 331
 332
 333
 334
 335
 336
 337
 338
 339
 340
 341
 342
 343
 344
 345
 346
 347
 348
 349
 350
 351
 352
 353
 354
 355
 356
 357
 358
 359
 360
 361
 362
 363
 364
 365
 366
 367
 368
 369
 370
 371
 372
 373
 374
 375
 376
 377
 378
 379
 380
 381
 382
 383
 384
 385
 386
 387
 388
 389
 390
 391
 392
 393
 394
 395
 396
 397
 398
 399
 400
 401
 402
 403
 404
 405
 406
 407
 408
 409
 410
 411
 412
 413
 414
 415
 416
 417
 418
 419
 420
 421
 422
 423
 424
 425
 426
 427
 428
 429
 430
 431
 432
 433
 434
 435
 436
 437
 438
 439
 440
 441
 442
 443
 444
 445
 446
 447
 448
 449
 450
 451
 452
 453
 454
 455
 456
 457
 458
 459
 460
 461
 462
 463
 464
 465
 466
 467
 468
 469
 470
 471
 472
 473
 474
 475
 476
 477
 478
 479
 480
 481
 482
 483
 484
 485
 486
 487
 488
 489
 490
 491
 492
 493
 494
 495
 496
 497
 498
 499
 500
 501
 502
 503
 504
 505
 506
 507
 508
 509
 510
 511
 512
 513
 514
 515
 516
 517
 518
 519
 520
 521
 522
 523
 524
 525
 526
 527
 528
 529
 530
 531
 532

10 The method of recording with no blank
spaces in the leading end of the sheet has been
described.

Regarding recording with no blank spaces in the left and right ends of the recording sheet 13, if the carriage scanning direction positions of the recording sheet and the carriage 30 are in ideal states, it is possible to perform recording with no blank spaces by executing recording to the limit of the sheet end. In an actual case, however, because of dependence on the sheet

Specifically, recording data is set to be wider than the set size of the recording sheet 13 by amounts L1 and Lr shown in Fig. 23. In the regions of L1 and Lr, the arrangements of the rib rows are predetermined so as to prevent the presence of ribs on the platen 11. This constitution prevents the sticking of ink droplets on the ribs of the platen 11 even if ink droplets are discharged outside the left or right end of the recording sheet, thereby enabling recording with no blank spaces to be performed. In addition, as recording data, it is necessary to prepare data

having a length, which is obtained by adding L1 and Lr to the width of the recording sheet 13. In the case of this constitution, when a recording sheet having an unknown sheet width is inserted, although ink droplets may be stuck to the ribs of the platen 11, the sheets of standardized sizes are used in most cases, and thus there are no problems for practical purposes.

Next, description will be made of recording with no blank spaces in the rear end portion of the sheet by referring to the flowchart of Fig. 25, illustrating the recording operation of the rear end portion of the sheet.

In step S31, when the rear end of the recording sheet 13 is detected by a PE sensor, a recording operation is started on the rear end portion of the sheet. During the recording operation on the full surface of the sheet, the rear end portion of the recording sheet 13 is detected during the recording sheet conveyance in the middle of the recording operation, and thus the position of detecting the sheet rear end is stored in the memory.

Then, in step S32, determination is made as to the conveyance of the recording sheet 13 by a predetermined amount from the recording sheet rear end position previously detected and stored

100221"6E22001

in the memory. Specifically, determination is made as to whether the rear end portion of the recording sheet 13 is in the range of the discharge nozzle row 16 or not. If the sheet rear
5 end is determined to be in this range, then the process proceeds to next step.

Subsequently, in step S33, the second region of the rear end recording data is masked. Specific means is almost similar to that of the
10 recording with no blank spaces in the sheet leading end, and thus only brief description will be made. That is, the recording data to be masked in this step is one located in the place of the same phase as that for the platen rib row 11b, and
15 a region for random masking is provided in the boundary of the regions, where one-line recording is carried out in a divided manner. Now, the region for random masking will be described by referring to Fig. 20. In the drawing, a reference
20 numeral 113d denotes an integrated portion of the first region single portion and an already recorded region; and 113e a first region superposed portion. For the first region superposed region 113e, random masking is carried
25 out by using a random mask pattern similar to that for the superposed region of the leading end portion of the recording sheet. Also for the

Sub
328
1002221-6222001

recording end portion, it is necessary to prepare recording data having a length longer than that of the recording sheet 13 by foreseeing ink droplets to be discharged to the outside of the recording sheet 13.

Then, in step S34, a first region is recorded by the first scanning of the carriage 30. The recording operation is similar to that for the recording with no blank spaces in the sheet leasing end portion. Thus, the sticking of ink droplets onto the platen rib row 11b is prevented, and ink droplets discharged to the outside of the recording sheet 13 are directly absorbed and recovered by the platen ink absorber 12. Fig. 20 shows a state after the end of this recording operation of one line, where a region 113c integrating the region recorded before the sheet rear end recording with the first recording region by the first scanning, and a first region superposed portion 113e recorded with a 50% duty by random masking, are formed on the recording sheet 13.

Subsequently, in step S35, the recording sheet 13 is conveyed by a predetermined amount. The rear end of the recording sheet 13 after the conveyance by the predetermined amount is within the range of the discharge nozzle row 16a, and the

Sub
B28
(Contd)

T00222T"6EE2200T

amount of conveyance in this case should preferably be set equal to/lower than half of the length of the discharge nozzle row 16 in the recording sheet conveying direction.

Sub
B29

100222T 6E2200T

5 Then, in step S16, the first region of the rear end recording data is masked. This masking is carried out for recording a portion unrecorded in steps S33 and S34. In other words, the recording data to be masked in this step is data
10 located in the place of the same phase as that for the platen rib row 11a. Now, description will be made of a region to be subjected to random masking by referring to Fig. 21. In the drawings, a reference numeral 113f denotes a rear end second
15 region superposed portion within the same range as that of the above-described rear end first region superposed portion; and 113g a rear end second region single portion. For the rear end second region superposed portion 113f, random masking is
20 carried out by using a random mask having a complementary relation with the random mask used for the rear end first region superposed portion 113e.

Then, in step S37, a second region is
25 recorded by the second scanning of the carriage 30. The recording operation is similar to that for recording with no blank spaces in the sheet

Sub
B29
(Contd)

leading end portion. Thus, the sticking of ink droplets onto the platen rib row 11a is prevented, and ink droplets discharged to the outside of the recording sheet 13 are directly absorbed and
5 recovered by the platen ink absorber 12. Fig. 21 shows a state after the end of the recording operation of one line, where the region 113c already recorded by step S34 is integrated with a region 113d recorded in step S37, thereby
10 completing the recording on the full surface of the recording sheet 13.

Then, in step S38, the recording sheet 13 is expelled out of the recording apparatus. The expelling operation is carried out cooperatively
15 by the discharge roller 37 and the not-shown gear as described above.

The method of recording with no blank spaces in the sheet rear end portion has been described.

20 Therefore, since recording with no blank spaces in the leading end, in the left and right ends, and in the rear end can be performed, it is possible to carry out recording with no blank spaces on the full surface of a predetermined
25 recording sheet.

In the embodiment, the ribs of the platen rib row are arrayed at equal intervals. However,

the invention is not limited to such an arrangement, and the ribs may be arranged at ununiform intervals. In such a case, each rib of the platen rib row A may be disposed roughly in the center between the adjacent ribs of the platen rib row B. The first and second regions 118 and 119 of the leading end recording data may respectively be set roughly in the centers between the ribs of the platen rib rows 11b and 11a, and a width of each in this case may be set about half of the rib interval.

In the embodiment, the one-line recording was carried out by a width equivalent to the length of the discharge nozzle row 16. However, the invention is not limited to such, and one-line recording may be carried out by a length equal to/lower than the length of the discharge nozzle row 16. This is very effective especially when recording resolution equal to/higher than the real resolution of the discharge nozzle row or the like is obtained.

As apparent from the foregoing, by constructing the ink jet recording apparatus according to the embodiment, it is possible to perform recording on the full surface of the recording sheet with no blank spaces without any complication or enlargement of the recording

apparatus, and without any cost increases. To obtain a recording result with no blank spaces, it is not necessary for the user himself to perform secondary processing after the recording operation, thus improving operability. Moreover, it is possible to perform high image quality recording without generating any white or black lines in the boundary of data block.

Fourth Embodiment

10 In the fourth embodiment, recording of one line in the recording sheet conveying direction is performed through one path by one recording head scanning operation outside a superposed region. However, the invention is not limited to such, and it is possible to perform recording in the recording sheet conveying direction by superposing a plurality of paths.

Next, description will be made of another embodiment with reference to the accompanying drawings.

Figs. 28A to 28G illustrate kinds of random masks when superposed regions are provided in main and sub scanning directions, and random masking is performed.

25 Figs. 28A to 28G show stage changes accompanied by the recording sheet conveying of the sub scanning direction. First, as shown in

Fig. 28A , recording of a first path is carried out in the main scanning direction by the width H of the recording head to convey the recording sheet in the sub scanning direction by LF. Then,
5 as shown in Fig. 28B, recording of a second path is carried out in the main scanning direction by the width H of the recording head to convey the recording sheet in the sub scanning direction by LF. Similarly, thereafter, recording is carried
10 out through paths one after another while conveying the recording sheet by a distance LF. When the recording head is passed through the same place of the recording sheet by four times, one-line recording is completed.

15 In Figs. 28A to 28F, one-line recording is carried out based on two divisions as in the case of the recording operation of the leading end or the rear end portion of the recording sheet in the third embodiment. In Fig. 28G and after, one-line
20 recording is carried out through one path.

Sub B30
~~According to the described embodiment, to complete recording by four recording head scanning operations, the recording width LH of the recording head for one operation is divided into
25 four portions to give random mask pattern rows different from one another. To achieve a 100% recording density in a complementary manner by~~

Sub
B30
(Contd)

four recording head scanning operations, four kinds of random mask patterns are provided for each. In other words, since sixteen patterns are necessary, definition is provided by using a 4x4 matrix in the embodiment.

Fig. 29 shows random mask patterns. A1 to A4 of Fig. 29, B1 to B4 of Fig. 29, C1 to C4 of Fig. 29, and D1 to D4 of Fig. 29 respectively show patterns of portions, in which recording is completed by four recording head scanning operations. E1 and E2 of Fig. 29, and F1 and F2 of Fig. 29 show patterns of portions, in which recording is completed by two recording head scanning operations. For example, if A1 to A4 of Fig. 29 are superposed at the same place, and recording is carried out, then a pattern a 100% duty is formed.

A random mask pattern is formed as shown in each of A1 to A4, B1 to B4, C1 to C4, D1 to D4, E1 to E2 and F1 to F2 of Fig. 29, and recording is performed based on the process shown in Figs. 28A to 28G. Accordingly, the recording of 100% duty is carried out from the leading end of the recording sheet 13 to the full surface. In this case, since recording is carried out by a plurality of ink discharge nozzles different for one-line recording, characteristic ununiformity of

the ink discharge nozzles is averaged out, making it difficult to see uneven concentration in the recording region.

As apparent from the foregoing, by
5 constructing the ink jet recording apparatus
according to the embodiment, compared with the
third embodiment, it is possible to perform better
recording on the full surface of the recording
sheet with no blank spaces.

10 Fifth Embodiment

In the third and fourth embodiments, the recording data block was divided to be rectangular. However, the invention is not limited to such, and a constitution described below may be employed.

15 Figs. 30A and 30B show the method of
dividing a recording data block according to the
fifth embodiment: each showing an example of a
recording data block divided into a parallelogram.
Fig. 30A shows a first region of leading end
20 recording data; and Fig. 30B a second region of
leading end recording data. Superposed portions
118 and 119 are respectively present in these
regions, and recording is performed by applying a
random mask pattern to a superposed portion. Also
25 with this constitution, a total length of the
recording data block in the main scanning
direction $L_{total}=L1+L2+L3+L4+L5+L6+L7+L8$ and $L9$

satisfies $L_{total} > L$ in a relation with a valid recording length L in the main scanning direction.

As apparent from the foregoing, by constructing the ink jet recording apparatus according to the embodiment, it is possible to perform high image quality recording without generating any visible white or black lines in the boundary of the data block.

Others

10 As the type of the recording apparatus of the invention comprising the recording mechanism, which uses the liquid injection recording head, other than one used as the image output terminal of the information processor of the computer or
15 the like, a copying device combined with a reader or the like, a facsimile device having a transmitting/receiving function, or the like may be employed.

As described above, according to each
20 embodiment, it is possible to perform recording on the full surface of the recording medium with no blank spaces without any complication or enlargement of the recording apparatus, and without any cost increases.

25 Since it is not necessary for the user himself to perform any secondary processing after the recording operation to obtain a recording

Sub
B3
"SECRET"

result with no blank spaces, operability can be improved.

Furthermore, since it is not necessary to add any secondary processing to the recording medium after the recording operation to obtain a recording result with no blank spaces, it is possible to obtain an extremely beautiful recording result without any degradation of recording medium finishing.

10 As apparent from the foregoing, according to the present invention, it is possible to perform recoding on the full surface of the recording sheet with no blank spaces without any complication or enlargement of the recording apparatus, and without any cost increases. 15 Moreover, it is possible to perform high image quality recording without generating any visible white or black lines in the boundary of the data block.

Sub
B32
10022122001